

ULD100 Complete Kit

Series



ULD100
Cover Sheet
D100**4" Wide Polymer Concrete Trench Drain Kit 3 - 99 Foot Complete****New Commercial Trench Drain / Driveway Drain
4 Inch Wide - A Class Galvanized Grates Standard****Complete System - Each Kit Includes:**

Specified number of 1 meter sections of trench drain
 Specified number of galvanized slotted grates with Lock Bars and Bolts
 2 - Solid End Caps and 1 - 4" End Outlet

Key advantages of the D100 Polymer Concrete Kits:

- Polymer Concrete Channels
- Load Classes up to C Class
- Stepped Edges for Lateral Protection
- External Width 6.1"
- Internal Width 3.9"
- Heights Between 5.5" - 9.25"

Number D100 Channel	Series D100 & U100K
--	--



SPORT SYSTEM

External width: 6.1"

Internal width: 3.93"

Length: 39.37"

Channel Reference	Height (in)		Hydraulic Section in. sq.	Outlet	
	A	B		Vertical	Horizontal
D100.00	5.51	3.93	13.3	4.33	—
D100.05	6.29	4.72	16.4	4.33	—
D100.10	7.28	5.71	21.39	4.33	4.33
D100.15	8.27	6.69	23.87	4.33	4.33
D100.20	9.25	7.67	27.59	4.33	4.33

Manufacturer



Specification

ULMA D100 Polymer Concrete linear drainage channel
 Polymer concrete edge for side protection
 Load Class up to C250
 Vertically and Horizontally channel aligning tongue and groove joints

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

Number D100K Accessories	Series D100 Galvanized end caps and lockdowns
---	---



End Outlet	Closed Encap	Min Height (in)	Max Height (in)
PE580x	T100DxxC	3.93	7.67




CS100-T

CS100-H

CS100 –H and CS100-T are locking devices to be used with the U100K and D100 series trench drain.

CS100-H is to be used with ductile iron or composite grates
 CS100-T is to be used with galvanized and stainless steel grates

Manufacturer 	Specification ULMA D100 Accessories SUPPLIED BY TRENCHIFY
--	--

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246


IIIIITRENCHIFY


www.trenchify.com

Number <p style="text-align: center;">GN100KCA</p>	Series <p style="text-align: center;">D100 & U100K A Galvanized Steel Slotted</p>
---	--



PART NUMBER	DIMENSIONS	FREE AREA
GN100KCA	39.4" [1000MM]	43.7 SQ. IN.



Manufacturer 	Specification <p>ULMA GN100KCA GALVANIZED STEEL SLOTTED TRENCH DRAIN GRATE WITH CLASS A LOAD RATING (3,500 LBS.—70 PSI), SUPPLIED BY TRENCHIFY</p>
--	--

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246


IIIIITRENCHIFY


www.trenchify.com

Number GP100KCA	Series D100 & U100K A Galvanized Steel Perforated
--------------------------------------	---



<u>PART NUMBER</u>	<u>DIMENSIONS</u>	<u>FREE AREA</u>
GP100KCA	39.4" [1000MM]	100.9 SQ. IN.



Manufacturer 	Specification ULMA GP100KCA GALVANIZED STEEL PERFORATED TRENCH DRAIN GRATE WITH CLASS A LOAD RATING (3,500 LBS.—70 PSI), SUPPLIED BY TRENCHIFY
--	--

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246


IIIIITRENCHIFY


www.trenchify.com

Number <p style="text-align: center;">IN100KCA</p>	Series <p style="text-align: center;">U100K A Stainless Steel Slotted</p>
---	--



PART NUMBER	DIMENSIONS	FREE AREA
IN100KCA	39.4" [1000MM]	33.5 SQ. IN.



Manufacturer 	Specification <p>ULMA IN100KCA STAINLESS STEEL SLOTTED TRENCH DRAIN GRATE WITH CLASS A LOAD RATING (3,500 LBS.—70 PSI), SUPPLIED BY TRENCHIFY</p>
--	---

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246


IIIIITRENCHIFY


www.trenchify.com

Number <p style="text-align: center;">GEHX100KCB</p>	Series <p style="text-align: center;">D100 & U100K B Galvanized Steel Mesh</p>
---	---



PART NUMBER	DIMENSIONS	FREE AREA
GEHX100KCB	39.3" [1000MM]	115.2 SQ. IN.



Manufacturer 	Specification <p>ULMA GEHX100KCB GALVANIZED STEEL MESH TRENCH DRAIN GRATE WITH CLASS B125 LOAD RATING (25,000 LBS.—580 PSI), SUPPLIED BY TRENCHIFY</p>
--	--

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246

IIIIITRENCHIFY

www.trenchify.com

Number PNH100KCAM/G	Series D100 & U100K A Composite Slotted
--------------------------------------	---





PNH100KCAM



PNH100KCAM-G

PART NUMBER	DIMENSIONS	FREE AREA
PNH100KCAM	19.6" [1000MM]	24.7 SQ. IN.



Manufacturer 	Specification ULMA PNH100KCAM COMPOSITE SLOTTED TRENCH DRAIN GRATE WITH CLASS A LOAD RATING (3,500 LBS.—70 PSI), SUPPLIED BY TRENCHIFY
--	--

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246


IIIIITRENCHIFY


www.trenchify.com

Number PE100KCBM	Series U100K A Composite Mesh
---------------------------------------	---



PART NUMBER	DIMENSIONS	FREE AREA
PE100KCBM	19.69" [499MM]	86.54 SQ. IN.



Manufacturer 	Specification ULMA PE100KCBM COMPOSITE MESH TRENCH DRAIN GRATE WITH CLASS B LOAD RATING (28,100LBS.—1170 PSI), SUPPLIED BY TRENCHIFY
--	--

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246


IIIIITRENCHIFY


www.trenchify.com

Number FNX100KCCM	Series D100 & U100K C Ductile Cast Iron Slotted
--	---



PART NUMBER	DIMENSIONS	FREE AREA
FNX100KCCM	19.6" [1000MM]	75.3 SQ. IN.



Manufacturer 	Specification ULMA FNX100KCCM DUCTILE CAST IRON SLOTTED TRENCH DRAIN GRATE WITH CLASS A LOAD RATING (56,200 LBS.—2341 PSI), SUPPLIED BY TRENCHIFY
--	---

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.

1-877-903-7246


IIIIITRENCHIFY


www.trenchify.com

<p>Number</p> <p>FNHX100KCCM</p>	<p>Series</p> <p>D100 & U100K</p> <p>C Ductile Cast Iron Slotted</p>
--	--



PART NUMBER	DIMENSIONS	FREE AREA
FNHX100KCCM	19.6" [1000MM]	26.9 SQ. IN.



<p>Manufacturer</p> 	<p>Specification</p> <p>ULMA FNHX100KCCM DUCTILE CAST IRON SLOTTED TRENCH DRAIN GRATE WITH CLASS A LOAD RATING (56,200 LBS.—2341 PSI), SUPPLIED BY TRENCHIFY</p>
--	---

DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trenchify and/or its manufacturers. TRENCHIFY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.